



Datasheet

Turntable FTM 0.8-0.2 mobile

Diameter 0.8 m, load capability 0.2 t

The turntable FTM 0.8-0.2 is designed for using in anechoic chamber. The turntable is transportable, two handles are provided for. Covering is made of aluminium.



Technical data:

Diameter:	0,8 m
Maximum total surface load admissible:	0.2 t
Height:	190 mm
Surface cover plate:	8 mm aluminium
Rotational speed:	Max. 3 rpm, adjustable on 30 steps
Slewing range:	+200 ° / -200 °
Accuracy:	0.1 °
Resolution:	0.1 °
Current consumption:	1.88 A
Connected load:	230 V / AC, 50/60 Hz
Temperature working range:	10 °C – +40 °C
Interface:	GRIP IEEE 488.2
Control cable:	Optical fibre cable, plastic, 660 nm, V-2Y 2X 1P980/1000 K-LWL, DUPLEX PE 2.2 mm
Drive unit:	Shielded and radio interference suppressed less than 10 dB below CISPR 22 class B

Communication interfaces:

The FTM series can be controlled by several Frankonia controllers. For more information about these options please ask for the following data sheet:

FC06 (Automatic controller with GPIB IEEE 488.2 interface)

Published by: FRANKONIA GmbH - Industriestrasse 16 - D-91180 Heideck
 Phone: +49-9177-98-5 00 - Fax: +49-9177-98-5 20 - E-mail: info@frankoniagroup.com
 Internet: www.frankoniagroup.com - Managing Director: Wolfgang Opitz
 Commercial Register: Amtsgericht Nürnberg - UST.-Ident-Nr.: HRB 8052 - VAT-Nr. DE 133565240

